### **MEETING ABSTRACT**





# How to get a bloodless intra-cardiac field in mini-invasive cardiac surgery

Ludwig K von Segesser<sup>1\*</sup>, Denis Berdajs<sup>2</sup>, Saad AbdelSayed<sup>1</sup>, Piergiorgio Tozzi<sup>1</sup>, Enrico Ferrari<sup>1</sup>

*From* World Society of Cardiothoracic Surgeons 25th Anniversary Congress, Edinburgh Edinburgh, UK. 19-22 September 2015

#### **Background/Introduction**

Minimally-invasive cardiac surgery is increasingly used in conjunction with peripheral cannulation. However, due to the relatively small diameter of the access vessels, thin walled venous cannulas are usually used in conjunction with augmentation. We have previously reported about 36F self-expanding cannulas which allow for remote cannulation and full flow (2.4 l/min m2) by gravity drainage. The new, smaller virtually wall-less 24F cannulas which pass through an 18F percutaneous orifice were designed for augmented venous drainage.

#### **Aims/Objectives**

The present study was designed to assess the in vivo performance of these, smaller, virtually wall-less, venous cannulas in comparison to traditional thin-wall cannulas.

#### Method

Remote cannulation was realized in 4 porcine experiments (75  $\pm$  3 kg) with percutaneous venous access, serial dilation up to 18F and insertion of either 19F thin wall, wire wound cannula or a smaller, virtually wall-less (24F Smart-canula ST). A standard MECC pump set with a centrifugal pump and a hollow fiber membrane oxygenator, but no in-line reservoir was used. Pump flow and the required pump inlet pressure were recorded for increasing pump speed from 1500 RPM to 3500 RPM (500 RPM increments).

#### Results

Pump flow accounted for  $1.2 \pm 0.2$  l/min for wall-less versus  $1.2 \pm 0.2$  l/min for thin wall at 1500 RPM,  $3.5 \pm 0.4$  versus  $3.1 \pm 0.4$  at 2500 RPM,  $5.6 \pm 0.4$  versus  $4.2 \pm 0.7$  at 3500 RPM. Pump inlet pressure accounted for  $-4 \pm 19$  mmHg versus  $2 \pm 13$  mmHg for 1500 RPM,  $-35 \pm 19$ 

<sup>1</sup>CHUV, Lausanne, Switzerland

versus -89  $\pm$  27 at 2500 RPM, and -90  $\pm$  21 versus -220  $\pm$  29 for 3500 RPM. For a pump inlet pressure of -88 mmHg, the mean pump flow was 4.5  $\pm$  0.8 l/min for the new smaller virtually wall-less venous cannula versus 3.1  $\pm$  l/min for control (p < 0.05).

#### **Discussion/Conclusion**

At the well accepted pump inlet pressure of -80 mmHg, the new, smaller, virtually wall-less, braided cannulas designed for use with augmentation provide unmatched venous drainage in vivo despite an 18F peripheral access. Early clinical analyses have confirmed these findings.

#### Authors' details

 $^{1}\mathrm{CHUV}$  , Lausanne, Switzerland.  $^{2}\mathrm{Toronto}$  General Hospital, Lausanne, ON, Canada.

Published: 16 December 2015

doi:10.1186/1749-8090-10-S1-A123 Cite this article as: von Segesser *et al*.: How to get a bloodless intracardiac field in mini-invasive cardiac surgery. *Journal of Cardiothoracic Surgery* 2015 **10**(Suppl 1):A123.

## Submit your next manuscript to BioMed Central and take full advantage of:

- Convenient online submission
- Thorough peer review
- No space constraints or color figure charges
- Immediate publication on acceptance
- Inclusion in PubMed, CAS, Scopus and Google Scholar
- Research which is freely available for redistribution

) BioMed Central

Submit your manuscript at www.biomedcentral.com/submit



© 2015 von Segesser et al. This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited. The Creative Commons Public Domain Dedication waiver (http://creativecommons.org/ public/domain/zero/1.0/) applies to the data made available in this article, unless otherwise stated.

Full list of author information is available at the end of the article